

ENERGY STAR Ratings - 6800 Metro

Hung

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1	None	1 2 3	0.34	34	1.7	0.3	0.55	0.63	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.04	30	1.7	0.3	0.49	0.56	4 5 6 7A 7B 8
	1" Grille And Over	1	0.04	28	1.7	0.3	0.44	0.5	4 5 6 7A
HS1V	None	1 2 3	0.34	37	1.42	0.25	0.5	0.62	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	34	1.42	0.25	0.45	0.55	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.04	31	1.42	0.25	0.4	0.49	4 5 6 7A 7B 8
HS4V	None	1 2	0.34	25	1.42	0.25	0.29	0.55	4 5 6 7A
	Under 1" Grille	1 2	0.04	23	1.42	0.25	0.26	0.49	4 5 6 7A
	1" Grille And Over	1 2	0.04	22	1.42	0.25	0.24	0.43	4 5 6 7A

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1



ENERGY STAR Ratings - 6800 Metro

Picture

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1									
	None	1 2 3	0.01	42	1.53	0.27	0.61	0.7	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	38	1.53	0.27	0.55	0.63	4 5 6 7A 7B 8
	1" Grille And Over	1 2 3	0.04	35	1.53	0.27	0.49	0.56	4 5 6 7A 7B 8
HS1V									
	None	1 2 3	0.01	37	1.31	0.23	0.45	0.55	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	43	1.31	0.23	0.55	0.68	4 5 6 7A 7B 8
	1" Grille And Over	1 2 3	0.04	40	1.31	0.23	0.5	0.62	4 5 6 7A 7B 8
HS4									
	None	1	0.01	27	1.48	0.26	0.33	0.62	4 5 6 7A
	Under 1" Grille	1	0.04	25	1.48	0.26	0.3	0.56	4 5 6 7A
	1" Grille And Over	1	0.04	23	1.48	0.26	0.27	0.5	4 5 6 7A
HS4V									
	None	1 2	0.01	28	1.25	0.22	0.26	0.49	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.04	31	1.25	0.22	0.32	0.61	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.04	29	1.25	0.22	0.29	0.54	4 5 6 7A 7B 8

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1



ENERGY STAR Ratings - 6800 Metro

Slider

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1									
	None	1 2 3	0.2	34	1.7	0.3	0.55	0.63	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.04	30	1.7	0.3	0.49	0.56	4 5 6 7A 7B 8
	1" Grille And Over	1	0.04	28	1.7	0.3	0.44	0.5	4 5 6 7A
HS1V									
	None	1 2 3	0.2	36	1.48	0.26	0.5	0.62	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.04	33	1.48	0.26	0.45	0.55	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.04	30	1.48	0.26	0.4	0.49	4 5 6 7A 7B 8
HS4V									
	None	1 2	0.2	25	1.42	0.25	0.29	0.55	4 5 6 7A
	Under 1" Grille	1 2	0.04	23	1.42	0.25	0.26	0.49	4 5 6 7A
	1" Grille And Over	1 2	0.04	22	1.42	0.25	0.24	0.43	4 5 6 7A

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1

