

ENERGY STAR Ratings - 2700 Metro

Hung

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1									
	None	1 2 3	0.385	35	1.65	0.29	0.55	0.63	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.385	31	1.65	0.29	0.49	0.56	4 5 6 7A 7B 8
	1" Grille And Over	1	0.385	28	1.65	0.29	0.44	0.5	4 5 6 7A
HS1V									
	None	1 2 3	0.385	37	1.42	0.25	0.5	0.62	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.385	34	1.42	0.25	0.45	0.55	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.385	31	1.42	0.25	0.4	0.49	4 5 6 7A 7B 8
HS4									
	None	1	0.385	22	1.59	0.28	0.3	0.56	4 5 6 7A
	Under 1" Grille	1	0.385	20	1.59	0.28	0.27	0.5	4 5 6 7A
	1" Grille And Over	1	0.385	18	1.59	0.28	0.24	0.44	4 5 6 7A
HS4V									
	None	1 2	0.385	26	1.36	0.24	0.29	0.55	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.385	24	1.36	0.24	0.26	0.49	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.385	23	1.36	0.24	0.24	0.43	4 5 6 7A 7B 8

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1



ENERGY STAR Ratings - 2700 Metro

Picture

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1									
	None	1 2 3	0.04	42	1.53	0.27	0.62	0.71	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	39	1.53	0.27	0.56	0.64	4 5 6 7A 7B 8
	1" Grille And Over	1 2 3	0.04	35	1.53	0.27	0.5	0.57	4 5 6 7A 7B 8
HS1V									
	None	1 2 3	0.04	45	1.25	0.22	0.56	0.69	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	42	1.25	0.22	0.51	0.62	4 5 6 7A 7B 8
	1" Grille And Over	1 2 3	0.04	39	1.25	0.22	0.46	0.56	4 5 6 7A 7B 8
HS4									
	None	1	0.04	27	1.48	0.26	0.33	0.63	4 5 6 7A
	Under 1" Grille	1	0.04	25	1.48	0.26	0.3	0.57	4 5 6 7A
	1" Grille And Over	1	0.04	23	1.48	0.26	0.27	0.51	4 5 6 7A
HS4V									
	None	1 2 3	0.04	33	1.19	0.21	0.33	0.61	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.04	31	1.19	0.21	0.3	0.55	4 5 6 7A 7B 8
	1" Grille And Over	1 2 3	0.04	30	1.19	0.21	0.27	0.49	4 5 6 7A 7B 8

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1



ENERGY STAR Ratings - 2700 Metro

Slider

GLAZING	GRILLES	ENERGY STAR ZONE	AIR RATING	ENERGY RATING	U-VALUE (Metric)	U-VALUE (Imperial)	SHGC	VT	9.36 CODE ZONES
HS1									
	None	1 2 3	0.27	35	1.65	0.29	0.55	0.63	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.27	32	1.65	0.29	0.49	0.56	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.27	29	1.65	0.29	0.44	0.5	4 5 6 7A 7B 8
HS1V									
	None	1 2 3	0.27	37	1.42	0.25	0.5	0.62	4 5 6 7A 7B 8
	Under 1" Grille	1 2 3	0.27	34	1.42	0.25	0.45	0.55	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.27	31	1.42	0.25	0.4	0.49	4 5 6 7A 7B 8
HS4									
	None	1	0.27	22	1.59	0.28	0.3	0.56	4 5 6 7A
	Under 1" Grille	1	0.27	20	1.59	0.28	0.27	0.5	4 5 6 7A
	1" Grille And Over	1	0.27	18	1.59	0.28	0.24	0.44	4 5 6 7A
HS4V									
	None	1 2	0.27	26	1.36	0.24	0.29	0.55	4 5 6 7A 7B 8
	Under 1" Grille	1 2	0.27	25	1.36	0.24	0.26	0.49	4 5 6 7A 7B 8
	1" Grille And Over	1 2	0.27	23	1.36	0.24	0.24	0.43	4 5 6 7A 7B 8

Legend:

Standards: U-Values = NFRC 100-1;

SHGC (Solar Heat Gain Coefficient) / VT (Visible Transmittance) = NFRC 200-1

