## ATMOSPHERE FOLDING DOOR: PRODUCT MATRIX SHEET - PVC DOOR

|   | · '                                  | Width (RO) |          | Height (RO) |          | PVC        |   | Sill         | Sill & Head | Frame    | Depth              |                    | Options             |            |                      |      |    |                      |  |  |                                       |                |
|---|--------------------------------------|------------|----------|-------------|----------|------------|---|--------------|-------------|----------|--------------------|--------------------|---------------------|------------|----------------------|------|----|----------------------|--|--|---------------------------------------|----------------|
| Panel   |                                      | Min (in)   | Max (in) | Min (in)    | Max (in) | Base Color | Ext (wrap)                                | Int (wrap)   | Туре        | Туре     | PVC (in)           | Alu. (in)          | Туре                | Glazing    | U-Factor<br>(W/m2-K) | SHGC | ER | 2020 ES<br>Compliant | 2015 NBC 9.36 Zone<br>Compliance (AB, SK,<br>MB) | 2020 NBC 9.36 Zone<br>Compliance (AB, SK,<br>MB) | NBC 9.36 Zone<br>Compliance (BC only) | Sealed<br>Unit |
| 2   | 2L, 2R,<br>1R1L                      | 56         | 75       | 36          | 96       |            |   |              |             |          |                    |                    |                     | E270 / i89 | 1.42                 | 0.24 | 22 | No                   | 4, 5, 6, 7A                                      | 4, 5, 6, 7A, 7B, 8                               | 4, 5, 6, 7A                           |                |
| 3   | 3L, 3R,<br>1L2R, 2L1R                | 75         | 109      | 36          | 96       |            | a. Black                                  |              | Low profile |          | 4"                 | 4"                 | Dual Pane           | E366 / i89 | 1.41                 | 0.18 | 19 | No                   | 4, 5, 6, 7A                                      | 4, 5, 6, 7A, 7B, 8                               | 4, 5, 6, 7A                           | Tempered with  |
| 4   | 4L, 4R,<br>1L3R, 3L1R                | 112        | 145      | 36          | 96       |            |   |              |             |          |                    |                    |                     | E180 / i89 | 1.47                 | 0.41 | 31 | No                   | 4, 5, 6, 7A, 7B, 8                               | 4, 5, 6, 7A, 7B, 8                               | 4, 5, 6, 7A                           |                |
| 5   | 5L, 5R,<br>1L4R, 2L3R,<br>3L2R, 4L1R | 140        | 178      | 36          | 96       | White      | b. White (with<br>white interior<br>only) | b. White     |             |          |                    |                    |                     |            |                      |      |    |                      |  |  | Preserve protection film              |                |
| Select Thermally Broken Aluminum door for over 5 panel requirement  Custom operation types available upon vendor approval |                                      |            |          |             |          | (Silly)    |   | requirement) |             | PVC (in) | Alu. (in)          | . (in)             | E270 / Clear / E270 | 1.27       | 0.21                 | 23   | No | 4, 5, 6, 7A, 7B, 8   | 4, 5, 6, 7A, 7B, 8                               | 4, 5, 6, 7A, 7B, 8                               |                                       |                |
|   |                                      |            |          |             |          |            |   |              |             |          | 4, 5, 6, 7A, 7B, 8 | 4, 5, 6, 7A, 7B, 8 | 4, 5, 6, 7A, 7B, 8  |            |                      |      |    |                      |  |  |                                       |                |
|   |                                      |            |          |             |          |            |   |              |             |          | 2 3/0              | 2 3/0              |                     |            |                      | ·    | ·  |                      |  | ·  |                                       |                |



Profile Material: UV Protect PVC (uPVC) Building Code Compliance: NAFS 11, PG30

Panel (ea) width: Min 28" / Max 34-1/4" Panel (ea) height: Min 28" / Max 96"

|  | Hardware   | Door Catch | Jamb Ext.     | Cladding,<br>Jamb<br>Adaptor &<br>Nail Fin | Retractible Rolling Screen  |              |            |                    |  |  |  |
|--|--|------------|---------------|--|---|--------------|------------|--------------------|--|--|--|
| Door<br>Handles                                  | Other  | Door Catch |               |  | Туре  | Height (in)  | Width (in) | Frame & Mesh Color |  |  |  |
| Solid brass,                                     | Locks are stainless steel, multi-<br>point systems with one hand |            | Not Available | Not Available                              | Single  | Custom as pe | Black      |                    |  |  |  |
| contemporary<br>style with a full<br>cylinder.   | operation for convenience and                                    |            |               |  | Double  | Custom as pe | Diack      |                    |  |  |  |
| Available in black & brushed chrome colors only. | Roller assemblies specially                                      |            |               |  | Available up to 20 feet as a single screen, and up to 40 feet as a double screen.  Adds 1-1/4" to frame on the inside |              |            |                    |  |  |  |